Status Report on the Borexino Muon Identification System

February 29, 1997

L. Oberauer, S. Schönert

on behalf of the TU-München Muon Group

Contents

1 Introduction

Borexino aims for detecting low energy solar neutrinos in a real time experiment. Crucial for the success of the project is a sufficient low background counting rate. Results obtained in an underground Counting Test Facility (CTF) at the Gran Sasso Laboratory showed very promising results about the internal radioactivity of Borexino detector materials. However, the CTF provided also the insight, that the remaining underground flux of cosmic muons may create a non negligible number of signals which cannot be distinguished from neutrino candidates, therefore jeopardizing the experiment. As a conclusion the setup of a muon identification system for Borexino was decided.

2 The Borexino Experiment

2.1 Neutrino Detection in Borexino

The aim of the solar neutrino experiment Borexino is to measure in real time the solar neutrino flux with a low energy threshold and with high statistics and energy resolution via the pure leptonic neutrino electron scattering process $\nu + e^- \rightarrow \nu + e^-$. Target is a liquid scintillator with fiducial mass of ca. 100t.

Motivation for Borexino comes from the long standing solar neutrino puzzle. Data analysis of the existing experiments leads to the assumption of severe suppression of the solar ^7Be-branch, which probably cannot be explained by modifications of the standard astrophysical model of the sun. The monoenergetic ^7Be-neutrinos give rise to a compton like recoil spectrum in Borexino. Its edge will be at 660 keV, significantly higher than the aimed energy threshold of ca. 250 keV. Thus ^7Be-neutrino detection is very efficient in Borexino. Depending on the physical scenarios different signal rates can be expected:

- Assuming validity of the standard model a counting rate for ^7Be-neutrinos, which would consist in this case purely as ν_e, of roughly 55/day in Borexino is expected.
- In scenarios of total neutrino flavour conversion (i.e. for neutrino mass differences $\Delta m^2 \approx 10^{-6} \rightarrow 10^{-5}\ eV^2$) a reduced flux down to approximately 12/day would be measured due to the lower cross section of $\nu_{\mu,\tau}$ scattering, which occurs only via neutral current interaction.
- In case of vacuum oscillations (i.e. for neutrino mass differences $\Delta m^2 \approx 10^{-10}\ eV^2$) Borexino would see a distinct time dependent periodical neutrino signal due to the seasonal eccentricity of the earth's orbit around the sun.
- For neutrino mass differences in the range of $\Delta m^2 \approx 10^{-7}\ eV^2$ and for large mixing Borexino should see a 'day/night' effect due to electron neutrino recovery during the path through the earth.

If Borexino is successful the measured ^7Be-flux can be compared with results from experiments using charge current reactions exclusively. These results may come from radiochemical measurements, but also from future real time experiments as it was proposed recently [1]. Total conversion of ^7Be ν_e to $\nu_{\mu,\tau}$ would mean no signal in charged current experiments and a reduced signal in Borexino, demonstrating neutrino flavour conversion uniquely.

Borexino also can serve for additional projects in neutrino physics. Search for a magnetic moment can be performed by means of terrestial neutrino sources by investigating the electron recoil shape at low momentum transfer. Via the inverse beta-decay $\bar{\nu_e} + p \rightarrow e^+ + n$ Borexino can look for signals from geophysical neutrinos [2, 3] as well as for neutrinos emitted by european nuclear power plants [4]. The latter would serve as a long baseline neutrino oscillation experiment probing the so-called large mixing angle solution for the solar neutrino problem.



Figure 1: *Schematic view of Borexino. The ultrapure scintillator (300t) inside a nylon vessel is shielded differentially by means of a liquid buffer (1040t), a steel sphere on which the tubes are mounted, and the outer water buffer which is contained in an external steel tank (diameter and height ca. 18m). A transparent nylon shroud hinders radon convection in the liquid buffer region. Additional tubes mounted on the outer surface of the steel sphere allow detection of penetrating muons via the Cherenkov effect. Each 6th of the inner tubes has no light guide, which enhances the acceptance of Cherenkov photons arising from muons intersecting the liquid buffer. This allows further muon identification. For explanation see text.*

2.2 The Detector and general Background Considerations

The detector is shielded successively from outer radioactivity by means of an onion-like structure. Here the adjacent inner layer serves as shielding and has to provide an increased purity in terms of internal radioactivity. Fig. 1 shows the experimental setup.

Borexino is placed in hall C of the underground laboratory at Gran Sasso, Italy. An overburden of ca. 3500 m.w.e. suppresses the cosmic muon flux to 1.1 $/hm^2$ and shifts the mean energy of the muons to 280 GeV. The outer part of the detector consists of a steel tank with 18m in height and diameter. Inside this 'external' tank a stainless steel sphere will support 2240 phototubes on the inside and 208 tubes at the outside. The steel is treated via an electropolishing procedure in such a way that the reflection of photons is suppressed. Most of the tubes inside the sphere will be equipped with light guides in order to increase the geometrical coverage and hence the energy resolution. Between external tank and sphere high purity water will serve as shielding against external gamma rays and as an active Cherenkov counter tagging penetrating cosmic muons[1]. The steel sphere will be filled with a transparent, high purity buffer liquid which itself holds a nylon sphere, filled with organic scintillator. Between the steel sphere and the scintillator region an additional nylon shroud hinders radon convection from the outer area towards the critical region.

The active scintillator mass will be around 300t. By means of time of flight measurements the event position can be reconstructed and a fiducial volume for solar neutrino interaction defined. Latter should be about 100t, establishing a counting rate of 55 neutrinos per day according to the standard solar model. The outer part of the scintillator sphere serves as active shielding.

The demands on purity in terms of radioactivity in Borexino, especially for the scintillator itself, are challenging. In order to be able to extract a clear signal from background events also in case of total flavour conversion, an intrinsic concentration in Uranium and Thorium of ca. 10^{-16} should not be exceeded significantly. The amount of $^{14}C/^{12}C$ must not be higher than $\approx 10^{-18}$. In order to test scintillating materials a large Counting Test Facility (CTF) has been built up in hall C of the underground laboratory at Gran Sasso, which resembles a small prototype (ca. 5t of scintillator) of Borexino. From beginning of 1995 until summer 1997 several tests about the feasibility of Borexino including procedures to maintain the purity of the scintillator have been performed, which showed encouraging results: $^{14}C/^{12}C = 1.94 \cdot 10^{-18}$, $^{238}U = (3.5 \pm 1.3) \cdot 10^{-16}\ g/g$, $^{232}Th = (4.4 \pm 1.5) \cdot 10^{-16}\ g/g$. A complete discussion of the CTF results including experimental techniques for further background suppression are given in [5] and [6]. Details about the experimental setup of the CTF can be found in [7].

Highly developed neutron activation analysis (NAA) of scintillation samples performed in Munich is now sensitive in the same regime, providing an independent test on the radiopurity and allowing tests on the secular equilibrium of the decay chains. With NAA an upper limit for uranium of $^{238}U < 2 \cdot 10^{-16}\ g/g$ (90% CL) has been obtained. In addition concentration values or limits have been measured by this method for various isotopes, including man-made nuclei for different detector materials. For details, see [8].

[1]The Outer Detector as described in Section 4.

Detector part	muon intersection rate (counts per day)
Inner vessel	2025
Steel sphere	5150
External tank	9900

Table 1: *Muon intersection rate for different parts of the Borexino detector.*

2.3 Muon background rates, CTF results

In calculating the muon rate expected for Borexino, we took the zenith muon distribution measured by the Macro collaboration at Gran Sasso and for the absolute normalization the experimental obtained value of 1.1 muon per hour and square meter. Tab. 1 shows the muon intersection rates for different parts of our detector.

About 10^4 muons per day hit the detector. Since the neutrino interaction rate will be in the range of a few counts per day in scenarios of full MSW-conversion, the overall muon leaking ratio into the neutrino window after all cuts must not exceed a value of about 10^{-4}.

Muon events inside the inner vessel will create pulses far above the solar neutrino spectrum. However, muons with tracks just between the steel sphere and the inner vessel may create signals just in the relevant energy region. According to Tab. 1 the rate of these muons is expected to be around $3 \cdot 10^3$ per day.

Since the timing of muon pulses should be different when comparing beta events, software cuts provide a tool to separate muons from neutrino candidates. In the CTF this was tested experimentally by means of a muon telescope installed on top of the CTF tank. Two position sensitive MWPC chambers with $3.42\,m^2$ sensitive area were installed and data taking occurred from August 1995 until end of 1996. Coincidences with the CTF showed that 24% of all muons intersecting the CTF water tank produce signals which are in the neutrino window between 250 keV and 800 keV. By measuring the meantime of the individual PM signals and comparing it to beta pulses (e.g. from the alpha beta delayed coincidences occurring in the radium chain) only 1.6% of all muons remain good candidates and have pulse heights within the neutrino window. However, this rejection factor still would be to small in Borexino.

The dimensions and the buffer material will be different in Borexino and from calculations one can expect better separation values (e.g. Section 5). However, these calculations certainly do not include possible "pathological" events which occur rarely, but can be of relevance in a low counting rate experiment as Borexino. For instance high energetic neutrons may enter the inner detector, even when the muon intersects the buffer region only. Without a hardware muon veto system those events could not be tagged.

There is hope in developing processes which might even improve the performance in purifying liquid scintillators. In this case, if no hardware muon veto system exists, the muon generated background would become dominating and condemn those developments as meaningless.

To base muon identification on software analysis alone would therefore be unreasonable. In addition such a method depends crucially on a reliable method to study systematic uncertainties. A hardware muon identification system would provide this method, because any possible software cut can be "calibrated" by the muon veto system. The rejection power as well as the acceptance for good events can then be determined experimentally. In Section 4, "Outer Detector", muon identification via the external Cherenkov detector is described quantitatively.

In addition a hardware muon identification system will provide a diagnostic tool for cosmogenic created nuclei with moderate long lifetimes as ^{11}C. It has the potential to define the spatial correlation between the muon track, the vertex of the shower creation, the location of neutron capture and of the delayed decay of produced radio isotopes. Though the possibility of muon track determination is not a primary objective of the Muon Identification System, it is considered to be a desirable feature of the system.

In a separate experiment we have recently measured the effective cross sections of radio isotope production in muon induced showers. Moreover, the activation profiles, i.e. the lateral probability distributions from the muon track have been determined. These results are reported in Section 6.

We conclude that the CTF results and calculations on the muon rates in Borexino demand the set up of a high efficient muon identification system which must not be based on software tools solely.

3 Strategy of the Muon Identification System

Careful analysis of the CTF-data clearly showed the necessity of an active muon identification system for Borexino. As discussed in the former section the leaking rate should not exceed a level of $\approx 10^{-4}$. This only can be achieved by a system based on several pillars. Our 'sub-systems' are:

- The *Outer Detector*: It will be a water Cherenkov detector, consisting of 208 photomultiplier (PMs) mounted on the outer surface of the steel sphere. We take advantage of the pure water shielding of Borexino. The Outer Detector is described in Section 4. Muons intersecting the water tank should be identified with high efficiency $>$ 95%.

- The *Inner Detector*: 2240 PMs are homogeneously distributed with 1866 of them equipped with light guides. Therefore about 16.7% of the tubes accept photons from all directions whereas PMs with light guides do accept photons mainly from the scintillator region. Cherenkov photons created along the track of the muon in the buffer liquid have a higher efficiency to hit a PM without light guide. Therefore, comparing the sum of photoelectrons from these tubes without light guides with the total sum of photoelectrons allows to separate between muon events and events from the scintillator. The Inner Detector is described in Section 5. Its separation efficiency of the Inner Detector should be $>$ 95%.

- The *Offline Analysis*: In analyzing the CTF data we have found several strategies to discriminate between beta- and muon events. Most of them are based on the unique timing distribution in the signal of a muon. Due to the different geometric situations these results cannot be fully adopted to the Borexino case. However, we have tested these strategies in Monte-Carlo calculations and found them to be sensitive also in Borexino. A description of these methods can be found in Section 5. The cut efficiency should be $>$ 95%.

These 'sub-systems' can be tested and calibrated mutually, thereby reducing systematic errors. This is, besides a combined identification efficiency of $\approx 10^{-4}$, an essential advantage of dividing the muon veto system in different parts.

Cosmogenic generated background due to muon interaction with nuclei from the detector material is discussed in Section 6.

4 Outer Detector (OD)

The region between the Outer Steel Tank (OST, volume 3500 m^3) and the Stainless Steel Sphere (SSS, diameter 13.70 m, volume 1350 m^3) is filled with 2150 m^3 of water. About 208 8" PM (EMI 9531) are mounted on the surface of the SSS viewing the water buffer. This part of the Borexino detector is named the Outer Detector (OD). The water buffer of the OD serves two functions: it shields (passively) against low-energy ambient radioactivity as gamma rays and neutrons coming from the rocks, and it provides an active water Cherenkov detection system for high energetic cosmic muons and their secondaries.

The PM surface density on the SSS amounts to 208 PM per 580 m^2, i.e. about 1 PM per 2.8 m^2. Two adjacent PMs are separated by a distance of typically 1.7 m. The shortest track length between OST and SSS is 2.15 m. The inner surface of the OST and the outer surface of the SSS are covered with 0.2 mm thick Tyvek plastic sheets. Tyvek is a white polyolefin plastic with a diffuse reflectivity of over 90% for visible light. The spectral reflectivity has been measured and is displayed in Fig. 2 together with the PM quantum efficiency and the primary photon spectrum. Cherenkov photons can impinge either directly on the photomultiplier cathode or after (several) reflections from the Tyvek film. The diffuse character of the reflection distributes the photons over a large surface area and hence increases the overall photoelectron (pe) yield as well as the number of triggered PMs.



Figure 2: *The spectral reflectivity of a 0.2 mm Tyvek plastic sheet is displayed together with the EMI 9351 Photo-cathode efficiency and the primary muon Cherenkov spectrum.*



Figure 3: *The left plot shows a simulation of the response of a 60 cm x 60 cm wave shifter plate. The color code reflects the probability that a photon which impinges on the panel is being transported to the PM. In the right plot, the photo electron gain is shown as a function of to the side length of the wave shifter panel. A uniform illumination is assumed which however is* **not** *the case in a Cherenkov cone.*

Optionally, the PMs will be equipped with wavelength shifter panels in order to further increase the pe-yield and the number of triggered PMs [9]. A wave shifter panel consists of an acrylic sheet of dimensions 60 cm x 60 cm x 1.3 cm which is doped at a concentration of 50 mg/l with bis-MSB (p-bis(0-methyl styryl) benzene, $C_{24}H_{22}$). The panel has a circular hole in its center for mounting a PM.

Photons which impinge on a wave shifter panel can be absorbed and remitted by the bis-MSB and guided via total internal reflection to the PM cathode. A quantitative model of the wave shifter panel is shown in Fig. 3.

The overall OD design is inspired by the Super-Kamiokande muon veto system. Many details on materials as well as on detector performance have been obtained from the BU Super-K group which we would like to acknowledge. The main difference between the Super-K and Borexino OD is that Borexino has a spherical symmetry with a relative smaller radius. It appears that this is favorable for the distribution of light over a wide surface area. This has an impact on the pe-yield and on the number of triggered PMs.

4.1 Mechanical Design for OD PMs

The PM encapsulation and sealing used in the OD are identical to the one used in the ID. In addition it is planed to use a teflon heat shrinking tube glued to the steel housing and glass of the PM. A sketch of the design is shown in Fig. 4. The mu-metal shield is reduced with respect to the design of the ID-PMs, however measurements have shown that the pe collection efficiency does not decrease more than 10% for a 'worst case magnetic field direction' in Borexino.